

REM. : MATERIAL SA ACCORDING CODE ASME, SEC.II, Ed 2007, NO ADDENDA
ПРИМЕЧ.: МАТЕРИАЛ ДЪЛГО СТАНДАРТА :

NOTE 1
ПРИМЕЧАНИЕ

KV>27J, ISO-V AT T=-41 ° C

NOTE 2
ПРИМЕЧАНИЕ

-100%UT ACC. TO SA788, S20-LEVEL DA

	NOTE 1			1	TUBE ТРУБА 3” sch.160 TR.Ø88.9x11.13-312	SA450	SA333 Gr.6	EN 10204-3.1	6.5,-			54
	NOTE 1			1	FLANGE DN80 PN40 ФЛАНЕЛ R13 80x88.9.s=11.13	DIN 2635 SA788	SA350 Gr.LF2 cl.1	EN 10204-3.1	4.8			53
				2+4SP	GASKET УПИЛОТЕННЕ DN 25 PN40 S=3,	TYPE SPV2J	S.S.304+GRAPHIT	EN 10204-2.2	0.1,-			52
				16+2SP	HEAVY HEX NUT M12 ГАЙКА	ANSI B18.2.2	SA194 Gr.7M	EN 10204-3.1	0.1,-		FABORY 22060	51
				8+1SP	STUD BOLD БОЛТ M12x70	ANSI B16.5	SA320 Gr.L7M	EN 10204-3.1	0.5,-		FABORY 22060	50
	NOTE 1			2	FLANGE DN50 PN40 ФЛАНЕЛ V13 50x57.s=8.74	DIN 2635 SA788	SA350 Gr.LF2 cl.1	EN 10204-3.1	5.6,-			49
	NOTE 1			2	TUBE ТРУБА 2” sch.XXS TR.Ø60.3x8.74-254	SA450	SA333 Gr.6	EN 10204-3.1	6.8,-			48
	NOTE 1			2	FLANGE DN50 PN40 ФЛАНЕЛ R13 50x60.3.s=11.07	DIN 2635 SA788	SA350 Gr.LF2 cl.1	EN 10204-3.1	2.9,-			47
				1	DETAIL 3 ДЕТАЛЪ 3				96.5,-		1-ZA-1322-1-4	46
	NOTE 1			1	BF FLANGE DN50 PN40 ФЛАНЕЛ V13 50x60.3	DIN 2527 SA788	SA350 Gr.LF2 cl.1	EN 10204-3.1	4,-			45
				2+4SP	GASKET УПИЛОТЕННЕ DN 25 PN40 S=3,	TYPE SPV2J	S.S.304+GRAPHIT	EN 10204-2.2	0.1,-			44
				16+2SP	HEAVY HEX NUT M12 ГАЙКА	ANSI B18.2.2	SA194 Gr.7M	EN 10204-3.1	0.1,-		FABORY 22060	43
				8+1SP	STUD BOLD БОЛТ M12x70	ANSI B16.5	SA320 Gr.L7M	EN 10204-3.1	0.5,-		FABORY 22060	42

